





# US Lube

## PERFORMANCE STANDARDS

- AFNOR NF E 48-690(Dry) & 691 (Wet)
- ASTM D6158 HM (2005)
- Bosch Rexroth
- Bosch Variable Volume Vane Pump
- Cincinnati Machine (MAG IAS) P- 68 ( ISO 32)
- Cincinnati Machine (MAG IAS) P- 69 ( ISO 68)
- Cincinnati Machine (MAG IAS) P- 70 ( ISO 46)
- Commercial Hydraulics ( Except Silver coated PM-500 series)
- DIN 51524 Part II
- DIN 51524 Part III HVLP
- Eaton brochure 03-401-2010
- Eaton Vickers I-286-S
- Eaton Vickers M-2950-S
- FZG A/8.3/90 Load test (DIN 51354) at 12th Stage level
- General Motor LH-03
- General Motor LH-04
- General Motor LH-06
- General Motors LS2 (2004)
- ISO 11158 HM (FDIS 2008)
- JCMAS HK P041 (2004)
- Parker Hannifin France (Denison) HF-0 (Revision J)
- Parker Hannifin France (Denison) HF-1, HF-2
- SAE MS1004
- Sauer Danfoss
- SEB 181 222 (2007)
- US Steel 126
- US Steel 127
- US Steel 136

THE AMERICAN TECHNOLOGY

Technical Data Sheet

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.